

iFACE201



iFace multi-biometric identification time attendance terminal adopts ZKSoftware's latest ZEM600 platform with ZK Face 5.0 algorithm and large capacity memory.

iFace series integrated 630MHz high speed ZK Multi-Bio processor and high definition infrared camera enables user identification in the dark environment.

The appearances of iFace series are designed by German designers who've stylishly integrated both functionality and aesthetics.

Details

<i>CPU</i>	<i>ZK Multi-Bio CPU 630 MHz</i>
<i>Memory</i>	<i>256M Flash, 64M SDRAM</i>
<i>Hardware Platform</i>	<i>ZEM600 Multi-Medium Development Platform</i>
<i>Camera</i>	<i>High Resolution Infrared Camera</i>
<i>Display</i>	<i>4.3" TFT touch screen</i>
<i>Face capacity</i>	<i>700</i>
<i>ID Card capacity</i>	<i>10,000</i>
<i>Logs capacity</i>	<i>100,000</i>
<i>Algorithm Version</i>	<i>ZK Face 5.0</i>
<i>2000mAh backup battery</i>	<i>Optional</i>
<i>Communication</i>	<i>TCP/IP,RS232/485</i>
<i>USB-HOST</i>	<i>2 USB-Host</i>
<i>Wireless Wi-Fi</i>	<i>Optional</i>
<i>Time attendance functions</i>	<i>Extendable Scheduled-bell, DLST, Self-Inquiry, Work Code, Short-Massage, T9 input, Webserver</i>
<i>Access control interfaces for Wiegand Signal</i>	<i>3rd party electric lock, door sensor, exit button</i>
<i>Optional functions</i>	<i>Output</i>
<i>Power supply</i>	<i>GPRS, serial printer, Mifare card, built-in POE</i>
<i>Verification Speed</i>	<i>12V3A</i>
<i>Operating temp</i>	<i>≤2 sec</i>
<i>Operating Humidity</i>	<i>0° - 45°C</i>
	<i>20%-80%</i>

Fabricant de Solutions

