

Z-6200F Auto-induction Guard Tour System

- RFID Auto - induction
- Super Low Power Consumption
- Wireless communication



Introduction

Read Method:

Auto-induction technology, no touch reading of RFID tags, breaking through the traditional contact card read, reducing the failure rate.

Super low power consumption:

Standby power consumption is 50 UA, camera battery CR123A; it can be working two years continuously.

Waterproof:

Completely sealed design can be used underwater.

Metal Structure:

Super metal liner, flexible rubber shell, super anti- wrestling, shockproof, anti-high temperature, low temperature.

Transmission mode:

No communication interface, wireless communication ,needn't ues cable to connect the Date Downloader , easy to use.

Card-reading Technology:

Switzerland EM induction card-reading technology.

Large Capacity:

Data storage up to 8000 records.

Safety:

Data can be stored for 30 years without power.

Direction:

Sound + LED

Support Language:

Support simplified and traditional Chinese, English and other languages

Fast download:

Downloading all the data only need 80 seconds.

Expansibility:

Support remote, GPRS communication.

How to use

Take the Z-6200F patrol device, and scan your guard ID card to login as the current user. Along the regulated patrol route; use the device to read the spot card by approaching the check spot. The check time and specific location will be collected and stored into the patrol device automatically. Through the Data Downloader upload the data to the specified computer. The patrol system software can deal with the data and display or print the result of the report.

Application fields

Applies to the buildings and residential property, public security, military, petroleum, railways, shopping malls, supermarkets, hotels, buildings, factories and mines, enterprises and institutions such as the patrol inspection.



Battery Leather Case Software

Properties

| | | | |
|-----------------------|----------------------------|---------------------------|---------------------------------|
| Card-Reading way | RFID Auto-induction reader | Working temperature | -20℃ – 70℃ |
| Storage Capacity | 8000PCS | Working humidity | 0~95% |
| Card-Reading Response | <0.2S | Standby power consumption | 50UA |
| Communication | Wireless Communication | Work power consumption | 8mA |
| Direction | LED+Sound | Battery life | Continuous use around two years |
| Dimension | 142 x 32 x 40MM | Battery | 3V lithium battery (CR123A) |
| Net Weight | 150g | Standardized accessories | Leather case |
| Baud rate | 57600Bps | | |